# भारतीय मानक Indian Standard

पेंट्स, इनेमल, वार्निश और संबंधित उत्पादों के पैकेजों की पैकिंग और मार्किंग के लिए — रीति संहिता

IS 5661: 2023

( पहला पुनरीक्षण )

Packing and Marking of Packages of Paints, Enamels, Varnishes and Allied Products — Code of Practice

(First Revision)

ICS 87.040

© BIS 2023



भारतीय मानक ब्यूरो BUREAU OF INDIAN STANDARDS

मानक भवन, 9 बहादुर शाह ज़फर मार्ग, नई दिल्ली - 110002 MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI - 110002

www.bis.gov.in www.standardsbis.in

#### **FOREWORD**

This Indian Standard (First Revision) was adopted by the Bureau of Indian Standards, after the draft finalized by the Paints, Varnishes, and Related Products Sectional Committee had been approved by the Chemical Division Council.

A large number of material specifications for paints, varnishes and allied products have created the need for a standard code of practice for packing, marking and packaging intended to serve the needs of indentors, suppliers and all those concerned with the use of these specifications.

This standard was first published in 1970. This revision has taken to bring out the standard in the latest style and format of the Indian Standard. In addition, the following changes have been made:

- a) Corrugated fibreboard boxes have become the popular choice when it comes to packing and storing goods due to its superior performance and easy handling over the other packing materials. Therefore, slotted corrugated fibreboard has been prescribed in place of rectangular solid wood case packaging;
- b) Considering smooth and efficient palletisation by the shrink film or stretch wrap the use of hay or bags filled with sawdust or rice husk has been redundant. Therefore, stretch film or stretch wrap has been prescribed for palletisation in order to prevent jolting. Also, the expanded polystyrene or polystyrene foam has been prescribed to prevent during transit;
- c) In order to trace the goods, batch and lot numbers have been added to the labelling provision of containers; and
- d) References of Indian Standards have been updated wherever required.

For the guidance of those concerned, an informative Annex A has been included listing containers normally used for packing of paints and allied products with the corresponding Defence Service Catalogue Numbers (DS Cat No.) and recommended materials to be packed.

The composition of the Committee responsible for the formulation of this standard is listed in Annex B.

# Indian Standard

# PACKING AND MARKING OF PACKAGES OF PAINTS, ENAMELS, VARNISHES AND ALLIED PRODUCTS — CODE OF PRACTICE

(First Revision)

#### 1 SCOPE

This code prescribes the methods of packing and marking of packages of paints, enamels, varnishes and allied products.

# 2 REFERENCES

The Standards given below contain provisions which through reference in this text, constitute provisions of this standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this Indian standard are encouraged to investigate the possibility of applying the most recent editions of these standards:

IS No.	Title
IS 1303 : 1983	Glossary of terms relating to paints (second revision)
IS 1394 : 1984	Glossary of terms relating to metal containers (third revision)
IS 1406 : 1995	Rectangular tins for liquids — Specification (fourth revision)
IS 1407 : 1980	Specification for round paint tins (second revision)
IS 1503 : 1988	Wooden packing cases — Specification (third revision)
IS 2552 : 1989	Steel drums (galvanized and ungalvanized) — Specification (third revision)
IS 2771 (Part 1): 2022	Corrugated fibreboard boxes — Specification: Part 1 General requirements (third revision)

# 3 TERMINOLOGY

For the purpose of this standard, definitions given in IS 1303, IS 1394 and the following shall apply.

**3.1 Tender Sample** — The sample submitted by the supplier with his tender.

# 4 PACKING AND MARKING

#### 4.1 Packing

**4.1.1** The supplier shall clearly state at the time of submitting tender sample, the capacities and types of containers in which the material shall be supplied.

- **4.1.2** The material shall be supplied in new clean and dry containers of the type and size specified.
- **4.1.2.1** The closure, lid screw-cap shall be well screwed in position to ensure an air-tight seal.
- **4.1.2.2** Each container shall contain the same net volume/weight of the material according to the capacity of the container.
- 4.1.3 Rectangular and Round Tins

# **4.1.3.1** Rectangular tins

These shall conform to IS 1406 and shall be of 500 ml, 1 000 ml or 5 000 ml capacity.

#### **4.1.3.2** *Round tins*

These shall conform to IS 1407 and shall be of 200 ml, 500 ml, 1 000 ml or 4 000 ml capacity.

**4.1.3.3** The filled containers shall be packed in slotted corrugated fibreboard boxes confirming to IS 2771 Part 1. Suitable lining and cushioning material shall be used to avoid damage in transit.

# **4.1.4** Dual Containers

- **4.1.4.1** Aluminium paste or powder shall be packed in the interior cylinder and the vehicle in the outer.
- **4.1.4.2** The container shall consist of two coaxial cylinders, one inside the other both fabricated from 0.40 mm tinplate. The outer cylinder provided with a suitable handle, having a full aperture tight fitting, double or single lever lid and an overall capsule covering the lid. The top and bottom rims shall be double seamed to cylindrical body, the side scam shall be grooved and sound soldered. The capacity shall be 4 litres with a maximum of 5 percent ullage space. The outer of the shall be painted suitably. The inner cylinder shall also be of sound construction with side scam, top and bottom rims and having a full aperture tight fitting single lever lid. The top rim shall be sound soldered concentrically to the lever lid of the outer cylinder. The size of the cylinder shall be capable of holding so much aluminium powder/paste as to give not less than 15 percent aluminium pigment in paint to be finally prepared.
- **4.1.4.3** Four filled containers shall be packed in a rectangular solid wood packing case of suitable

dimensions conforming cylinder to IS 1503 with suitable lining and cushioning materials. The maximum weight of each package shall not exceed 40 kg.

**4.1.4.4** The rectangular wooden packages shall be strapped or wired at two places. The straps shall be of galvanized mild steel, 1.83 mm to 2.64 mm thick. If wired, it shall be placed as close to the buttons as possible, but not over them.

#### **4.1.5** Drums and Kegs

- **4.1.5.1** Drums and kegs shall be of either galvanized or mild steel with recommended closures and shall conform to IS 2552. The capacity of drums or kegs shall be 5 litres, 10 litres and 20 litres.
- **4.1.5.2** The filled drums and kegs, comprising of full wagon load shall be loaded for despatch in full wagons as given in **4.1.5.3**.
- **4.1.5.3** The filled containers shall be properly packed and every precaution taken to avoid loss or damage in transit. The filled containers shall be wrapped in shrink film or stretch wrap. Expanded polystyrene or polystyrene foam might be used for specific cases. The containers themselves shall be packed tightly side by side where the bottom of the wagon has curved edges. Then curved empty space shall also be filled with bags filled with cushioning material. The second and subsequent tiers shall be loaded in a similar manner suitably stuffed with cushioning material. The bags shall be of *ad hoc* sizes for stuffing into crevices and vacant spaces.
- **4.1.5.4** Filled drums and kegs in small numbers, which are insufficient to make a full wagon load, shall be despatched loose.

# 4.2 Marking

# **4.2.1** Marking of Containers

The containers shall be marked with the following:

- a) Name and class of material;
- b) Name of the manufacturer and/or trade-mark, if any;
- c) Batch/Lot number;
- d) Volume/Weight of the material; and
- e) Date of manufacture.
- **4.2.1.1** A circular band of not less than 1.3 cm in width of the same colour as that of the contents of the containers except in the cases of oils, varnishes and thinners below the upper rim.
- **4.2.1.2** The supply when intended for defence users, the containers shall be marked with the

information given in **4.2.1** and the following:

- a) DS Cat No.; and
- b) Contract No.
- **4.2.1.3** Emergency procedure labels-general guidance for dealing with spillage and leakage and instruction for emergencies shall be marked.

# **4.2.2** Containers Containing Flammable Materials

All containers for storage and transport of this class of material, since classified as dangerous and flammable goods, shall in addition, comply with the requirement of latest issue of red tariff and requirements as laid down from time to time by the Chief Inspectorate of Explosives, Government of India, for packing, storage and transit of flammable liquids and the *Board of Trade Regulations* as applicable thereon for transport by steamers.

- **4.2.2.1** The containers shall also be marked 'HIGHLY FLAMMABLE LIQUID' in red letters and the flash point of the contents.
- **4.2.2.2** In case of drums, in addition to the information prescribed in **4.2.1**, the serial number of drums together with total number of drums in the same delivery shall also be stated.
- **4.2.2.3** In case of dual containers, in addition to the information prescribed in **4.2.1**, the following shall also be marked:

Mix the total quantity of aluminium powder/paste in the inner container with the varnish medium in the outer by constant stirring with a clean metal rod just prior to use.

**4.2.3** Marking of Rectangular, Solid Wood Packing Cases

Each case shall be legibly and indelibly marked on top and on one of the longer sides as follows:

- a) Name, and class of material;
- b) Quantity packed;
- c) Serial number of packages with total number of packages in the same delivery;
- d) Manufacturer's name and/or recognized trade-mark, if any; and
- e) Inscription of the words 'HIGHLY FLAMMABLE in 5 cm red block letters in case of packages of flammable materials like nitrocellulose paints, lacquers, thinners, etc.
- **4.2.3.1** When the material is intended for defence users, the case shall be marked with DS Cat No. and Contract No. also in addition to those given in **4.2.3.**

# ANNEX A

(Foreword)

# INFORMATION REGARDING TYPES OF CONTAINERS, THEIR SIZES, DS CAT NUMBER AND RECOMMENDED MATERIALS TO BE PACKED

Sl No.	Description	Capacity	DS Cat No.	Recommended Materials to be Packed	
		ml			
(1)	(2)	(3)	(4)	(5)	
i)	Rectangular tins	500	8 110 – 000 015	Paints, tinners, enamels and	
		1 000	$8\ 110-000\ 016$	varnishes classified under both classes A and B flammable	
		5 000	8 110 – 000 017	liquids (see Notes 1 and Note 2)	
ii)	Round tins	200	8 110 – 000 011	, ,	
		500	$8\ 110-000\ 012$	nitrocellulose dopes and finishes classified under both	
		1 000	8 110 - 000 013	Classes A and B flammable	
		4 000	8 110 – 000 014	liquids (see Notes 1 and Note 2)	
iii)	Dual containers	5 000	-	Aluminium paints classified under both Classes A and B flammable liquids (see Note 1 and Note 2)	
iv)	Drums, mild steel	3 000	8 110 - 000 003		
		5 000	$8\ 110-000\ 004$	Paints, enamels and varnishes	
		15 000	$8\ 110-000\ 005$	classified under Class B (see Note 2) flammable liquids only.	
		20 000	8 110 - 000 006		
v)	Drums, galvanized	5 000	8 110 – 000 001 –	Thinners, paints, enamels,	
		25 000	8 110 - 000 002 _	varnishes and nitrocellulose dopes and finishes classified under flammable liquids both Classes A and Class B (see Note 1 and Note 2)	
vi)	Kegs, mild steel	3 000	8 110 – 000 007		
		5 000	8 110 - 000 008		
		10 000	8 110 – 000 009	Putty and pastes	
		15 000	8 110 - 000 010		

#### NOTES

 $<sup>{\</sup>bf 1} \ Flammable \ liquids, the \ vapours \ of \ which \ have \ flash \ point \ below \ 24.4\ ^{\circ}\!C \ are \ classified \ as \ highly \ flammable \ liquids, \ Class \ A.$ 

<sup>2</sup> Flammable liquids, the vapours of which have flash point between 35.0  $^{\circ}$ C and 24.4  $^{\circ}$ C (both inclusive) are classified as flammable liquids, Class B.

#### ANNEX B

(Foreword)

#### COMMITTEE COMPOSITION

Paints, Varnishes and Related Products Sectional Committee, CHD 20

Organization Representative(s)

Institute of Chemical Technology, Mumbai PROF P. A. MAHANWAR, (*Chairperson*)

Akzo Nobel India Limited, Gurugram, Shri Sanatan Hajra

Asian Paints Ltd, Mumbai Shri Rajeev Kumar Goel

SHRI RAJES BARDIA (Alternate)

Bharat Heavy Electricals Ltd, Tiruchirapalli Shri K. Srinivasan

SHRI V. RAJESHKHARAN (Alternate)

Berger Paints India Ltd, Howrah Shri Tapan Kumar Dhar

SHRI SWAGATA CHAKROBORTY (Alternate)

Central Building Research Institute, Roorkee DR SUKHDEO R. KARADE

DR P. C. THAPLIYAL (Alternate)

Central Public Works Dept., New Delhi, SHRI AMAR SINGH

SHRI M. L. PRASAD (Alternate)
SHRI DIVAKAR AGRAWAL (Alternate)

Controllerate of Quality Assurance (Materials), Ministry

of Defence (DGQA), Kanpur

DR GURBACHAN SINGH SHRI A. K. PATRA (*Alternate*)

Consumer Voice, New Delhi Shri M. A. U. Khan

Engineers India Limited, New Delhi SHRI S. GHOSHAL

SHRI A. SATYA SRIDHAR (Alternate)

Harcourt Butler Technical University, Kanpur PROF P. K. KAMANI

PROF ARUN MAITHANI (Alternate)

Institute of Chem. Technology, Mumbai PROF V. V. SHERTUKADE

Indian Institute of Technology, Mumbai PROF SMRUTIRANJAN PARIDA

Indian Paints Association, Kolkata Shri Subroto Banerjee

DR M. B. GUHA (Alternate)

Indian Small Scale Paint Association Shri Mukesh Goyal

SHRI H. SATHYANARAYAN (Alternate I) SHRI NIRAV RAVESHIA (Alternate II)

J K Cement Limited, Kanpur Shri Rana Pratap Singh

DR PRITI PILLAY (Alternate)

Kansai Nerolac Paints Ltd, Mumbai Shri Laxman Nikam

Shri Manoj Kumar Somani (*Alternate*)

Meta Chem Paints and Adhesives Private Limited,

Nashik

SHRI BISWANATH PANJA

SHRI HEMANT KULKARNI (Alternate)

Ministry of Defence, Department of Standardization,

New Delhi

LT COL PRAVEEN DEO

SHRI V. K. CHHABRA (Alternate)

Ministry of Industry, New Delhi National Test House (ER), Kolkata

istry of Industry, New Delhi Shri Nand Lal

SHRIMATI P. NATARAJAN
DR A. B. MONDAL (Alternate)

Naval Materials Research Laboratory (NMRL), Thane

DR T. K. MAHATO

DR G. GUNASEKARAN (Alternate)

Organization

Representative(s)

Office of the Micro Small & Medium Enterprises

(MSME), New Delhi

SHRIMATI M. ANNABACKIAM

SHRIMATI M. S. RAMMIYA (Alternate)

Paint and Coating Technologists Association, Kanpur

SHRI USHENDRA SINGH

Pidilite Indusries Ltd, Mumbai

SHRI VIVEK KUMAR SAXENA (Alternate)

ridinic industres Eta, Walioar

SHRI RAMESH KASHYAP SHRI SUSHANT PANGAM (Alternate)

SHRI K. P. SINGH (Alternate)

Research Designs & Standards Organization, Lucknow

SHRI P. K. BALA

Shriram Institute for Indl. Research, Delhi

SHRI A. K. MAJUMDAR

SSPC India Chapter, Kolkata, Mumbai

Dr Buddhadeb Duari

SHRI ANIL SINGH (Alternate)

The Shipping Corporation of India Ltd, Mumbai

SHRI N. K.TRIPATHI

SHRI SUSHIL ORAON (Alternate)

In Personal Capacity (Flat 1303, Blooming Heights, Pacific Enclave, Powai, Mumbai, 400076)

DR B. P. MALLIK

In Personal Capacity (2, Block Mann Street, Kolkata 700013)

DR SUNIL KUMAR SAHA

Director General, BIS

A. K. LAL SCIENTIST 'F'/SENIOR DIRECTOR AND HEAD (CHEMICAL) [REPRESENTING DIRECTOR

GENERAL (*Ex-officio*)]

Member Secretary
Shri Pushpendra Kumar
Scientist 'B'/Assistant Director
(Chemical), BIS

This Pade has been Intentionally left blank

This Pade has been Intentionally left blank

#### **Bureau of Indian Standards**

BIS is a statutory institution established under the *Bureau of Indian Standards Act*, 2016 to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

# Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Head (Publication & Sales), BIS.

# **Review of Indian Standards**

Amendments are issued to standards as the need arises on the basis of comments. Standards are also reviewed periodically; a standard along with amendments is reaffirmed when such review indicates that no changes are needed; if the review indicates that changes are needed, it is taken up for revision. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition by referring to the website-www.bis.gov.in or www.standardsbis.in.

This Indian Standard has been developed from Doc No.: CHD 20 (21329).

# **Amendments Issued Since Publication**

Amend No.	Date of Issue	Text Affected	

# **BUREAU OF INDIAN STANDARDS**

# **Headquarters:**

Manak Bhavan, 9 Bahadur Shah Zafar Marg, New Delhi 110002

Telephones: 2323 0131, 2323 3375, 2323 9402 Website: www.bis.gov.in

I crep	25. 2526 6161, 2626 6676, 2626 5 162	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
Regional	Offices:		Telephones
Central	: 601/A, Konnectus Tower -1, 6 <sup>th</sup> Floor, DMRC Building, Bhavbhuti Marg, New Delhi 110002		<i>Telephones</i> 2323 7617
Eastern	: 8 <sup>th</sup> Floor, Plot No 7/7 & 7/8, CP Block, Sector V, Salt Lake, Kolkata, West Bengal 700091		2367 0012 2320 9474
Northern	: Plot No. 4-A, Sector 27-B, Madhya Marg, Chandigarh 160019		265 9930
Southern	: C.I.T. Campus, IV Cross Road, Taramani, Chennai 600113		2254 1442 2254 1216
Western	: Plot No. E-9, Road No8, MIDC, Andheri (East), Mumbai 400093		2821 8093

Branches: AHMEDABAD. BENGALURU. BHOPAL. BHUBANESHWAR. CHANDIGARH. CHENNAI. COIMBATORE. DEHRADUN. DELHI. FARIDABAD. GHAZIABAD. GUWAHATI. HIMACHAL PRADESH. HUBLI. HYDERABAD. JAIPUR. JAMMU & KASHMIR. JAMSHEDPUR. KOCHI. KOLKATA. LUCKNOW. MADURAI. MUMBAI. NAGPUR. NOIDA. PANIPAT. PATNA. PUNE. RAIPUR. RAJKOT. SURAT. VISAKHAPATNAM.